

# 16CHANNEL DVR



## Features:

- H.264 & dual-stream video compression
- Mobile view on 3G/Wifi enabled device
- Real-time recording
- Simultaneous VGA and CVBS outputs
- Embedded WEB server for remote access
- Alarm for video loss, motion detection, tampering and abnormal signal

## SPECIFICATIONS:

Brand	Hikvision
Type	HD DVR
Video Compression:	H.264
Analog and HD-TVI video input:	8-ch,BNC interface (1.0Vp-p, 75 Ω)
Supported camera types:	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
IP Video Input:	1-ch 1080P
Video Input Interface:	BNC (1.0 Vp-p, 75Ω)
Audio Compression:	G.711u
Two-way Audio:	1-ch RCA(2.0Vp-p, 1kΩ)
HDMI/VGA Output:	1920 × 1080 / 60 Hz,1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz

Recording resolution:	Main stream: 1080P (non-real-time) / 720P / WD1/ VGA / 4CIF / CIF;Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame Rate:	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Sub-stream:	1/16 fps ~ Real time frame rate
Video Bit Rate:	32 Kbps-6 Mbps
Audio Output:	1-ch RCA(2.0 Vp-p, 1kΩ)
Audio Bit Rate	64kbps
Dual Stream:	Support
Playback Resolution:	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Synchronous Playback:	8-ch
Remote connections:	128
Network protocols:	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Interface Type:	1 SATA Interface
Capacity:	Up to 4TB capacity for each disk
Network Interface:	1; 10M / 100M self-adaptive Ethernet interface
USB Interface:	2 USB 2.0 Interfaces
Serial Interface:	1; standard RS-485 serial interface, half-duplex
Power Supply:	12V DC
Consumption:	≤ 15W
Working Temperature:	-10 °C ~+55 °C (14 °F ~ 131 °F)
Working Humidity:	10% ~ 90%
Chassis:	1U chassis
Dimension:	315 × 242 × 45mm (12.4 × 9.5 × 1.8 inch)
Weight:	≤ 1.5Kg (3.3lb)