

# 8CHANNEL NVR



## Features:

Third-party network cameras supported

Up to 6 Megapixels resolution recording

HDMI and VGA output at up to 1920×1080P resolution

4/8/16-ch network cameras can be connected with 40M/80M/160M incoming bandwidth

Up to 2 SATA interfaces

Support network detection, including network delay, packet loss, etc.

## SPECIFICATIONS:

Brand	Hikvision <a href="#">View all HIKVISION Products</a>
-------	---

Model No:	DS-7608NI-E1-8
-----------	----------------

## VIDEO/AUDIO INPUT

Type	Network Video Recorder <a href="#">View all Network Video Recorder Products</a>
------	---

IP video input	8-ch
----------------	------

Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
---------------------	---------------------------

## NETWORK

Incoming bandwidth:	80Mbps
---------------------	--------

Outgoing bandwidth	80Mbps
--------------------	--------

Remote connection	128
-------------------	-----

## VIDEO/AUDIO OUTPUT

HDMI/VGA output:	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
------------------	--

Recording Resolution:	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Frame Rate:	Main stream: 50 fps (P) / 60 fps (N) Sub-stream: 50 fps (P) / 60 fps (N)
Audio Output:	1-ch, RCA (Linear, 1kΩ)
Synchronous Playback	8-ch
<b>DECODING</b>	
Live view / Playback:	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Capability	5-ch1080P
<b>HARD DISK</b>	
SATA:	1 SATA interfaces for 1 HDD
Capacity:	Up to 4TB for each disk
<b>EXTERNAL INTERFACE</b>	
Network Interface:	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
USB Interface:	1 × USB 2.0 and 1 × USB 3.0
Alarm In:	4-ch(optional)
Alarm Out	1-ch(Optional)
<b>GENERAL</b>	
Power Supply:	12V DC
Consumption(without hard disk and POE)	≤ 10W
Working Humidity:	-10 °C ~ +55 °C (+14 °F~ + 131 °F)
Working Humidity:	10 % ~ 90 %
Chassis:	1U chassis
Dimensions:	315 × 230 × 45mm (12.4 × 9.0 × 1.8 inch)
Weight(without HDD)	≤ 1 Kg